

GRACE ROUGH TERRAIN FORKLIFT



Model	RT-3000	RT-3500A	RT-4000	RT-5000
Dimensions	4200*1800*2700mm	4200*1800*2700mm	4400*1850*2800mm	4400*1900*2900mm
Engine model	YUNNEI YN27GBZ(490 Turbocharged))	YUNNEI YN27GBZ(490 Turbocharged)	YUNNEI YN38GBZ(4102 Turbocharged)	YUNNEI YN38GBZ(4102 Turbocharged)
Fork length	1220mm	1220mm	1520mm	1520mm
Rated lift weight	3000kg	3500kg	4000kg	5000kg
Turning radius	3500mm	3500mm	4500mm	4500mm
Platform ground clearance	300mm	300mm	350mm	350mm
Axle	Small wheel side weight cast steel bridge	Small wheel side weight cast steel bridge	Middle wheel steel bridge	Large wheel steel bridge
Tire	20.5/70-16	20.5/70-16	20.5/70-16	16/70-20
Gantry width	160mm	160mm	180mm	180mm
Overall weight	4000kg	4200kg	5000kg	5500kg
Engine power	40kw	58kw	76KW	76KW
Gradeability	≤38°	≤38°	≤38°	≤38°
Rated lifting height	3000-6000mm	3000-6000mm	3000-6000mm	3000-6000mm
Front ground clearance	250-350mm	250-350mm	300-380mm	300-380mm
Drive type	4X4	4X4	4X4	4X4
Gearbox	265 Double high and low speed large pump torque converter	265 Double high and low speed large pump torque converter	280 Double high and low speed torque converter	280 Double high and low speed torque converter
Frame	Hinged thick 3mm	Hinged thick 3mm	Hinged thick 3.5mm	Hinged thick 3.5mm

PRODUCT DETAILS

DETAILED DESCRIPTION



SPECIAL OFF ROAD TIRE

ENGINEERING SPECIAL OFF-ROAD TIRE HAS GOOD GRIP AND LONG ANTI-SKID AND WEAR-RESISTANT LIFE.

FIRM FLAT FORK

STRONG AND DURABLE FLAT FORK LIFT, STRONG LOAD, HIGH EFFICIENCY.





HYDRAULIC STEERING

THE HYDRAULIC STEERING IS EASY TO OPERATE, FLEXIBLE AND EASY TO TURN.

BRAND ENGINE

BRAND POWER, FULL HORSEPOWER, LOW FUEL CONSUMPTION, HIGH EFFICIENCY AND LONG SERVICE LIFE.



SAFETY CAB

CUSTOMIZED RUBBER PLATE FRAME CAB WITH GOOD SEALING, SMALL VIBRATION AND NO NOISE.

